

LS355

ONE WAY  
NUMERIC PAGER



*Enhanced  
features make  
this pager  
small in size  
yet big on  
convenience.*



#### **LS355 NUMERIC PAGER**

This easy-to-carry pager has a host of advanced features that help users stay in touch. There are 16 message slots, with 6 individual addresses. Messages are time stamped, and can be erased selectively or all at once. There's memory backup, a message full indicator, discrete vibration, and a large backlit display for superb readability.

Quick User Guide:

- 6 Individual Addresses (cap codes)
- 16 Message Slots
- 12-digit LCD Backlit Display with 4 Icons
- Message Preview
- Message Time Stamping
- Message Full Indication
- Selective Erase/Erase All

#### **LS355 NUMERIC PAGER**

##### ***Model Number***

A03GRS5961AA - VHF

A04GRS5961AA - UHF

***Advanced Features That Help  
Users Stay In Touch***

***Superb Readability***

### LS355 PAGER FEATURES

- 6 Individual Addresses (cap codes)
- 16 Message Slots
- 12-digit LCD Backlit Display with 4 Icons
- Message Preview
- Message Time Stamping
- Message Full Indication
- Selective Erase/Erase All
- Saves Messages When Off or Changing Battery
- Time and Date on Standby
- Full Function Self Test
- Unread Message Indication
- Out of Range Indication
- Low Battery Alert and Indication
- RS232 Programmable
- POCSAG Technology
- AGC Function

### ORDERING INFORMATION

Phone:

**1-800-422-4210**

TTY Customers:

**1-866-522-5210**

U.S. Federal Government:

**1-800-826-1913**

Motorola Online Users:

<https://www.motorola.com/businessonline>



### VHF FREQUENCY RANGE

Band A	143-152 MHz
Band B	153-162 MHz
Band C	163-174 MHz

### UHF FREQUENCY RANGE

Band A	450-459 MHz
Band B	460-470 MHz

### SPECIFICATIONS

Transmission Speed:	512 / 1200 / 2400 Baud Rate
Modulation:	FSK +/- 4.5KHz
Channel Band Width:	25 KHz
Intermediate Frequency:	21.4MHz / 455KHz
Sensitivity:	5uv/m(512BPS) / 7uv/m(1200BPS) 9uv/m(2400BPS)
Adjacent Channel Selectivity:	55dB @ +/-25KHz
Image Frequency Rejection:	50dB
Spurious Response Rejection:	50dB
Intermodulation Rejection:	50dB
Alert Response:	75Bspl @ 30CM
Ambient Working Temperature:	-5 degrees C to - 40 degrees C
Battery:	1.5 Volt "AA" Alkaline x 1
Dimension:	68mm(l) x 50mm(w) x 18mm(h)

